

Bibliography

- [1] S. E. Holland, “Fully depleted charge-coupled devices,” SNIC Symposium, (Stanford, CA), 2006.
- [2] B. E. Burke, J. L. Tonry, M. J. Cooper, D. J. Young, A. H. Loomis, P. M. Onaka, and G. A. Luppino, “Development of the orthogonal-transfer array,” *SPIE Proc.* **6068**, 2006.
- [3] J. R. Janesick, *Scientific Charge-Coupled Devices*, SPIE-The International Society for Optical Engineering, Bellingham, Washington, 2001.
- [4] I. S. McLean, *Electronic Imaging In Astronomy: Detectors and Instrumentation*, Praxis Publishing, Chichester, UK, 1997.
- [5] P. Martinez and A. Klotz, *A Practical Guide to CCD Astronomy*, Cambridge University Press, Cambridge, UK, 1998.
- [6] I. Deyhimy, R. C. Eden, R. J. Anderson, and J. S. Harris Jr., “A 500-MHz GaAs charge-coupled device,” *Applied Physics Letters* **36**, January 1980.
- [7] S. Lauxtermann, G. Izrael, P. Seitz, H. Bloss, J. Ernst, H. Firla, and S. Gick, “A mega-pixel high speed CMOS imager with sustainable gigapixel/sec readout rate,” *2001 IEEE Workshop on Charge-Coupled Devices and Advanced Image Sensors* , June 2001.
- [8] T. Brandt, “High-speed CMOS imagers are flexible,” *Laser Focus World* , February 2004.
- [9] J. L. Lowrance, V. J. Mastrocola, G. F. Renda, P. K. Swain, R. Kabra, M. Bhaskaran, J. R. Tower, and P. A. Levine, “Ultrahigh-frame CCD imagers,” *SPIE Proc.* **5210**(67), 2004.
- [10] M. Downing, G. Finger, D. Baade, N. Hubin, O. Iwert, and J. Kolb, “Detectors for AO wavefront sensing,” *SPIE Proc.* **7015**(62), 2008.
- [11] J. Janesick, T. Elliot, and J. Tower, “CMOS detectors: Scientific monolithic CMOS imagers come of age,” *Laser Focus World* , July 2008.

- [12] M. Sirianni and M. Mutchler, "Radiation damage in HST detectors," in *Scientific Detectors For Astronomy 2005*, pp. 171–178, Springer Netherlands, 2006.
- [13] C. J. Bebek, J. H. Bercovitz, D. E. Groom, S. E. Holland, R. W. Kadel, A. Karcher, W. F. Kolbe, H. M. Oluseyi, N. P. Palaio, V. Prasad, B. T. Turko, and G. Wang, "Fully depleted back-illuminated p-channel CCD development," *SPIE Proc.* **5167**, pp. 50–62, 2004.
- [14] J. Janesick, J. T. Andrews, and T. Elliot, "Fundamental performance differences between CMOS and CCD imagers: Part 2," *SPIE Proc.* **6276**, 2006.
- [15] S. V. W. Beckwith et al., "The Hubble ultra deep field," *The Astronomical Journal* **132**, pp. 1729–1755, November 2006.
- [16] J. Mack, J. Biretta, S. Baggett, and C. Proffitt, "WFPC2 dark current vs. time," *Instrument Science Report WFPC2 2001-2005*, 2001.
- [17] P. Magnan, "Detection of visible photons in CCD and CMOS: A comparative view," *Nuc. Inst. and Meth.* **504**, pp. 199–212, 2003.
- [18] J. W. Beletic, "Optical and infrared detectors for astronomy: Basic principles to state-of-the-art," in *Optics in Astrophysics*, pp. 123–154, Springer Netherlands, 2005.
- [19] M. Bigas, E. Cabruja, J. Forest, and J. Salvi, "Review of CMOS image sensors," *Microelectronics Journal* **37**, pp. 443–451, 2006.
- [20] E. Goujou, P. Gorria, E. Fauvet, M. Robert, and G. Cathebras, "Study and characterization of photosensitive cells in ASICs," *Industrial Electronics, Control and Instrumentation* **2**, pp. 911–914, 1994.
- [21] S. K. Mendis, S. E. Kemeny, R. C. Gee, B. Pain, C. O. Staller, Q. Kim, and E. R. Fossum, "CMOS active pixel image sensors for highly integrated imaging systems," *IEEE Journal of Solid-State Circuits* **32**(2), 1997.
- [22] A. Hoffman, M. Loose, and V. Suntharalingam, "CMOS detector technology," in *Scientific Detectors For Astronomy 2005*, pp. 377–402, Springer Netherlands, 2006.
- [23] J. W. Beletic, R. Blank, D. Gulbransen, D. Lee, M. Loose, E. C. Piquette, T. Sprafke, W. E. Tennant, M. Zandian, and J. Zino, "Teledyne Imaging Sensors: Infrared imaging technologies for astronomy and civil space," *SPIE Proc.* **7021**(20), 2008.
- [24] A. Moore, Z. Ninkov, and W. J. Forrest, "Quantum efficiency overestimation and deterministic cross talk resulting from interpixel capacitance," *Opt. Eng.* **45**(7), p. 076402, 2006.

- [25] Y. Bai, J. Bajaj, J. W. Beletic, M. C. Farris, A. Joshi, S. Lauxtermann, A. Petersen, and G. Williams, "Teledyne Imaging Sensors: Silicon CMOS imaging technologies for x-ray, uv, visible and near infrared," *SPIE Proc.* **7021**(01), 2008.
- [26] K. D. Munck, D. S. Tezcan, T. Borgers, W. Ruythooren, P. D. Moor, S. Sedky, C. Toccafondi, J. Bogaerts, and C. V. Hoof, "High performance hybrid and monolithic backside thinned CMOS imagers realized using a new integration process," *Electron Devices Meeting*, pp. 1–4, Dec. 2006.
- [27] B. Burke, P. Jorden, and P. Vu, "CCD technology," *Experimental Astronomy* **19**, pp. 69–102, 2005.
- [28] J. Ohta, *Smart CMOS Image Sensors and Applications*, Taylor and Francis Group, Boca Raton, FL, 2008.
- [29] C. Hong and R. I. Hornsey, "CMOS active pixel sensor with in-pixel contrast stretch," *2001 IEEE Workshops on CCDs and Advanced Image Sensors*, June 2001.
- [30] J. P. Crooks, S. E. Bohndiek, C. D. Arvanitis, R. Speller, H. XingLiang, E. G. Villani, M. Towrie, and R. Turchetta, "A CMOS image sensor with in-pixel ADC, timestamp, and sparse readout," *IEEE Sensors Journal* **9**, pp. 20–28, 2009.
- [31] D. X. D. Yang, B. Fowler, and A. E. Gamal, "A nyquist-rate pixel-level ADC for CMOS image sensors," *IEEE Journal of Solid-State Circuits* **34**(3), 1999.
- [32] J. Vaillant and F. Hirigoyen, "Optical simulation for CMOS imager microlens optimization," *SPIE Proc.* **5459**, 2004.
- [33] J. Yoshida, "OmniVision adopts backside illumination technology for CMOS imager," *EE Times*, May 2008.
- [34] J. W. Beletic, "IR focal-plane arrays enable imaging that is out of this world," *Laser Focus World*, October 2007.
- [35] B. Pain and E. R. Fossum, "A review of infrared readout electronics for space science sensors," tech. rep., Jet Propulsion Laboratory, July 1993.
- [36] G. H. Rieke, "Infrared detector arrays for astronomy," *Annual Review of Astronomy And Astrophysics* **45**, pp. 77–115, 2007.
- [37] Y. Bai, S. G. Bernd, J. R. Hosack, M. C. Farris, J. T. Montroy, and J. Bajaj, "Hybrid CMOS focal plane array with extended UV and NIR response for space applications," *SPIE Proc.* **48**, 2003.

- [38] S. Kilcoyne, N. Malone, M. Harris, J. Vampola, and D. Lindsay, "Silicon p-i-n focal plane arrays at raytheon," *SPIE Proc.* **7082**, 2008.
- [39] L. M. Simms, D. F. Figer, B. J. Hanold, D. J. Kerr, D. K. Gilmore, S. M. Kahn, and J. A. Tyson, "First use of a HyViSI H4RG for astronomical observations," *SPIE Proc.* **6690**, August 2007.
- [40] B. N. Dorland, G. S. Hennessy, N. Zacharias, D. G. Monet, H. Harris, C. Rollins, P. Shu, L. Miko, B. Mott, A. Waczynski, and E. Kan, "Laboratory and sky testing results for the TIS H4RG-10 4kx4k, 10 micron visible CMOS-hybrid detector," *SPIE Proc.* **6690**, 2007.
- [41] M. J. McCaughean, *The Astronomical Application of Infrared Array Detectors*. PhD thesis, University of Edinburgh, 1988.
- [42] S. L. Solomon, *Near Infrared Spectroscopic Imaging of NGC 7023 and Charge Trapping in InSb Photodiode Arrays*. PhD thesis, University of Rochester, 1998.
- [43] A. C. Moore, *Operating, Testing, and Evaluating Hybridized Silicon P-I-N Arrays*. PhD thesis, Rochester Institute of Technology, 2005.
- [44] H. Bushouse, C. Skinner, and J. MacKenty, "The STSCI NICMOS pipeline: CALNICA, single image reduction," June 10, 1996.
- [45] Z. Ivezic et al., "LSST: From science drivers to reference design and anticipated data," *arXiv:astro-ph/0805.2366v1* , 15 May 2008.
- [46] B. R. Hancock, T. J. Cunningham, K. McCarty, G. Yang, C. Wrigley, P. G. Ringold, R. C. Stirbl, and B. Pain, "Multi-megarad (Si) radiation tolerant integrated CMOS imager," *SPIE Proc.* **4306**, 2001.
- [47] M. Bruzzi, "Radiation damage in silicon detectors for high-energy physics experiments," *IEEE Transactions on Nuclear Science* **48**(4), 2001.
- [48] A. D. Falcone, D. N. Burrows, Y. Bai, M. Farris, R. Cook, and S. Bongiorno, "Hybrid CMOS x-ray detectors: The next generation for focused x-ray telescopes," *SPIE Proc.* **6686**, 2007.
- [49] R. J. Dorn, S. Eschbaumer, G. Finger, L. Mehrgan, M. Meyer, and J. Stegmeier, "A CMOS visible silicon imager hybridized to a Rockwell 2RG multiplexer as a new detector for ground based astronomy," *SPIE Proc.* **6276**, 2006.
- [50] S. W. Han and E. Yoon, "Low dark current CMOS image sensor pixel with photodiode structure enclosed by p-well," *Electronics Letters* **42**(20), 2006.

- [51] C. Y. Wu, Y. C. Shih, J. F. Lan, C. C. Hsieh, C. C. Huang, and J. H. Lu, "Design, optimization, and performance analysis of new photodiode structures for CMOS active-pixel-sensor (APS) imager applications," *IEEE Sensors Journal* **4**(1), 2004.
- [52] G. Finger, R. Dorn, M. Meyer, L. Mehrgan, A. Moorwood, and J. Stegmeier, "Interpixel capacitance in large format CMOS hybrid arrays," *SPIE Proc.* **6267**, 2006.
- [53] S. M. Sze, *Physics of Semiconductor Devices: Second Edition*, John Wiley & Sons, 1981.
- [54] S. Kayali, G. Ponchack, and R. Shaw, "GaAs MMIC reliability assurance guideline for space applications," Tech. Rep. 96-25, Jet Propulsion Laboratory, December 1996.
- [55] R. F. Pierret, *Volume I: Semiconductor Fundamentals*, Addison-Wesley, second ed., 1988.
- [56] Y. Bai, M. C. Farris, A. Joshi, J. R. Hosack, J. Bajaj, and J. T. Montroy, "Recent progress of hybrid CMOS visible focal plane array technology," *SPIE Proc.* **5902**, 2005.
- [57] M. Kurata, *Numerical Analysis for Semiconductor Devices*, Lexington Books, 1982.
- [58] W. W. Gärtner, "Depletion-layer photoeffects in semiconductors," *Physical Review* **116**(1), 1959.
- [59] B. J. Rauscher, O. Fox, P. Ferruit, R. J. Hill, A. Waczynski, Y. Wen, W. Xia-Serafino, B. Mott, D. Alexander, C. K. Brambora, R. Derro, C. Engler, M. B. Garrison, T. Johnson, S. S. Manthripragada, J. M. Marsh, C. Marshall, R. J. Martineau, K. B. Shakoorzadeh, D. Wilson, W. D. Roher, M. Smith, C. Cabelli, J. Garnett, M. Loose, S. Wong-Anglin, M. Zandian, E. Cheng, T. Ellis, B. Howe, M. Jurado, G. Lee, J. Nieznanski, P. Wallis, J. York, M. W. Regan, D. N. B. Hall, K. W. Hodapp, T. Böoker, G. D. Marchi, P. Jakobsen, and P. Strada, "Detectors for the james webb space telescope near-infrared spectrograph I: Readout mode, noise model, and calibration considerations," *arXiv:0706.2344v1* , 15 Jun 2007.
- [60] M. Loose, J. Beletic, J. Garnett, and M. Xiu, "High-performance focal plane arrays based on the HAWAII-2RG/4RG and the SIDECAR ASIC," *SPIE Proc.* **6690**, 2007.
- [61] M. Vadipour, "Capacitive feedback technique for wide-band amplifiers," *IEEE Journal of Solid-State Circuits* **28**, January 1993.
- [62] D. F. Figer, M. Agronin, J. Balleza, R. Barkhouser, L. Bergeron, G. R. Greene, S. R. McCandliss, B. J. Rauscher, T. Reeves, M. W. Regan, U. Sharma, and H. S. Stockman, "The Independent Detector Testing Laboratory and the NGST detector program," *SPIE Proc.* **4850**(981), 2003.
- [63] I. S. Glass, *Handbook of Infrared Astronomy*, Cambridge University Press, Cambridge, UK, 1999.

- [64] J. R. Janesick, G. B. Soli, T. S. Elliot, and S. A. Collins, "Effects of proton damage on charge coupled devices," *SPIE Proc.* **1447**(87), 1991.
- [65] D. F. Figer, B. J. Rauscher, M. W. Regan, E. Morse, J. Balleza, L. Bergeron, and H. S. Stockman, "Independent testing of JWST detector prototypes," *SPIE Proc.* **5167**(270), 2004.
- [66] B. Pain and T. J. Cunningham, "Fundamentals of CMOS imagers, operation, performance, trends." Lecture Notes, 2009.
- [67] O. Yadid-Pecht, B. Mansoorian, E. R. Fossum, and B. Pain, "Optimization of noise and responsivity in cmos active pixel sensors for detection of ultra low light levels," *SPIE Proc.* **2019**, pp. 125–136, 1997.
- [68] H. Tian and A. E. Gamal, "Analysis of 1/f noise in CMOS APS," *SPIE Proc.* **3965**, pp. 168–176, 2000.
- [69] H. Tian, B. Fowler, and A. E. Gamal, "Analysis of temporal noise in CMOS photodiode active pixel sensor," *IEEE Journal of Solid-State Circuits* **36**(1), 2001.
- [70] C. Leyri, S. Piloret, M. Marin, M. Minondo, and H. Jaouen, "Random telegraph signal noise SPICE modeling for circuit simulators," *Solid State Devices Research Conference* **37**, 2007.
- [71] A. M. Fowler and I. Gatley, "Demonstration of an algorithm for read-noise reduction in infrared arrays," *Astrophysical Journal* **353**(33), 1990.
- [72] J. D. Garnett and W. J. Forrest, "Multiply sample read limited and background limited noise performance," *SPIE Proc.* **1946**(395), 1993.
- [73] J. D. Offenberg, D. J. Fixsen, M. A. Nieto-Santisteban, R. Sengupta, J. C. Mather, and H. S. Stockman, "Uniform data sampling: Noise reduction & cosmic rays," *ASP Conference Series: Astronomical Data Analysis Software and Systems X* **238**, 2001.
- [74] A. M. Fowler and I. Gatley, "Noise reduction strategy for hybrid IR focal plane arrays," *SPIE Proc.* **1541**, 1991.
- [75] R. Chapman, S. Beard, M. Mountain, D. Pettie, and A. Pickup, "Implementation of a charge integration system in a low background application," *SPIE Proc.* **1235**, 1990.
- [76] N. Bezawad and D. Ives, "High-speed multiple window readout of HAWAII-1RG detector for a radial velocity measurement," *SPIE Proc.* **6276**, 2006.
- [77] I. M. Peters, E. W. Bogaart, W. Hoekstra, A. C. M. Kleimann, and J. T. Bosiers, "Very-low dark current in FF-CCDs," *IEEE Workshop on Charge-Coupled Devices and Advanced Image Sensors*, (Karuizawa, Japan), 2005.

- [78] R. J. Dorn, S. Eschbaumer, D. N. B. Hall, G. Finger, L. Mehrgan, M. Meyer, and J. Stegmeier, “Evaluation of the Teledyne SIDECAR ASIC at cryogenic temperature using a visible hybrid H2RG focal plane array in 32 channel readout mode,” *SPIE Proc.* **7021-29**, 2008.
- [79] J. R. Janesick, *Photon Transfer*, SPIE-The International Society for Optical Engineering, Washington, 2007.
- [80] D. F. Figer, M. Regan, and E. Morse, “Independent testing of silicon PIN detector arrays for LSST,” *American Astronomical Society Meeting 2005* **36**, p. 1528, 2004.
- [81] P. Horowitz and W. Hill, *The Art of Electronics*, Cambridge University Press, Cambridge, UK, 1989.
- [82] W. H. Press, W. T. Vetterling, S. A. Teukolsky, and B. P. Flannery, *Numerical Recipes in C: The Art of Scientific Computing*, Cambridge University Press, New York, NY, 1992.
- [83] D. Bacon, A. Refregier, and R. Ellis, “Detection of weak gravitational lensing by large-scale structure,” *Mon. Not. Roy. Astron. Soc.* **318**, p. 625, 2000.
- [84] C. Sterken, *Astronomical Photometry*, Springer Verlag, New York, LLC, 2002.
- [85] G. Verdoes, R. Vermeij, E. Valentijn, and K. Kuijken, “The secondary standards program for OmegaCAM at the VST,” *arXiv:astro-ph/0612469v1* , 18 Dec 2006.
- [86] P. Stetson, “Some factors affecting the accuracy of stellar photometry with CCDs,” *DAO Preprint* , September 1988.
- [87] S. Jester et al., “The Sloan Digital Sky Survey view of the Palomar-Green bright quasar survey,” *The Astronomical Journal* **130**(3), pp. 873–895, 2005.
- [88] B. N. Dorland, R. Dudik, G. S. Hennessy, A. Waczynski, B. J. Rauscher, P. K. Shu, and J. E. Hubbs, “Laboratory and sky testing of the second generation Teledyne Imaging Sensor (TIS) 16.7 megapixel visible/near-IR CMOS-hybrid array H4RG-10 A2,” *SPIE Proc.* **7439**, 2009.
- [89] A. U. Landolt, “UBV photoelectric sequences in the celestial equatorial selected areas 92-115,” *The Astronomical Journal* **78**(959), 1973.
- [90] A. U. Landolt, “UBVRI photometric standard stars in the magnitude range $11.5 < V < 16.0$ around the celestial equator,” *Astrophysical Journal* **104**(1), 1992.
- [91] C. A. Gullixson, P. C. Boeshaar, J. A. Tyson, and P. Seitzer, “The BjRI photometric system,” *The Astrophysical Journal Supplement* **99**, pp. 281–293, 1995.