

# Contents

<b>Abstract</b>	<b>iv</b>
<b>Preface</b>	<b>v</b>
<b>Acknowledgments</b>	<b>vii</b>
<b>1 Introduction</b>	<b>1</b>
1.1 A Very Brief History of Visible Detectors in Astronomy . . . . .	1
1.2 The CCD: Astronomy's Champion Workhorse . . . . .	4
1.2.1 CCD Operation . . . . .	4
1.2.2 Drawbacks of the CCD in Astronomy . . . . .	7
1.2.3 Where the CCD Wins in Astronomy . . . . .	11
1.3 CMOS: Motivation for a New Detector . . . . .	13
1.3.1 Overview of CMOS Imager Operation . . . . .	14
1.3.2 Monolithic CMOS Imagers . . . . .	15
1.3.3 Hybrid CMOS Imagers . . . . .	16
1.3.4 Advantages of CMOS Arrays for Astronomy . . . . .	19
1.3.5 Disadvantages of CMOS Arrays in Astronomy . . . . .	22
<b>2 Overview of Silicon PIN Detectors</b>	<b>24</b>
2.1 PIN Diodes . . . . .	24
2.1.1 General Discussion of PIN Diodes . . . . .	24
2.1.2 PIN Diode Circuit Equivalent Model . . . . .	26
2.1.3 Punch Trough Voltage . . . . .	27
2.2 HyViSI Detector . . . . .	29
2.2.1 HyViSI PIN Diode . . . . .	29
2.2.2 The HyViSI Pixel . . . . .	34

<b>3 Hybrid Imager Features</b>	<b>40</b>
3.1 Full Frame Mode . . . . .	40
3.1.1 Up the Ramp Terminology . . . . .	42
3.2 Window Mode . . . . .	42
3.2.1 Variation of Multiple Window Readout Sequences . . . . .	44
3.3 Guide Mode . . . . .	44
3.4 Reference Pixels . . . . .	45
3.5 Readout Electronics: SIDECAR ASIC . . . . .	49
3.5.1 Pre-Amplification Stage . . . . .	51
3.5.2 Conversion Gain . . . . .	54
3.5.3 Averaging Multiple Channels . . . . .	55
3.5.4 Noise Performance vs. Pixel Time . . . . .	58
3.5.5 Reference Voltages for SIDECAR when Connected to an HxRG . . . . .	59
<b>4 Laboratory Testing of SiPIN Detectors</b>	<b>62</b>
4.1 Description of Laboratory Setups and Devices Tested . . . . .	62
4.2 Pixel Classification and Operability . . . . .	65
4.2.1 Dead or Railed Pixels . . . . .	65
4.2.2 Hot Pixels . . . . .	65
4.2.3 Open Pixels . . . . .	66
4.2.4 Volcanoes . . . . .	66
4.2.5 Summary of Pixels . . . . .	67
4.3 Conversion Gain and Nodal Capacitance . . . . .	68
4.3.1 Contributions to the Gain . . . . .	68
4.3.2 Electronics Gain – $G_{AMP}$ & $G_{A/D}$ . . . . .	68
4.3.3 Unit Cell Source Follower Gain – $G_{UC}$ . . . . .	69
4.3.4 Output Source Follower Gain – $G_{OUT}$ . . . . .	69
4.3.5 Net Conversion Gain – $G_{NET}$ . . . . .	71
4.3.6 Nodal Capacitance – $G_{PIXEL}$ . . . . .	72
4.3.7 Results for HyViSI Detectors . . . . .	73
4.4 Read Noise . . . . .	75
4.4.1 Sources of Read Noise in Hybrid CMOS Detectors . . . . .	75
4.4.2 Noise Reduction Techniques . . . . .	78
4.4.3 HyViSI Measurements . . . . .	81
4.5 Dark Current . . . . .	84
4.5.1 Sources of Dark Current . . . . .	84
4.5.2 Estimating Dark Current . . . . .	84
4.5.3 HyViSI Dark Currents . . . . .	86

4.5.4	Reset Anomaly in HyViSI . . . . .	87
4.6	Quantum Efficiency . . . . .	90
4.6.1	PIN Diode Quantum Efficiency . . . . .	90
4.6.2	HyViSI Detective Quantum Efficiency (DQE) . . . . .	90
4.7	Linearity/Well Depth . . . . .	92
4.7.1	Sources of Nonlinearity in HyViSI Detectors . . . . .	92
4.7.2	Measurements of Nonlinearity in HyViSI Detectors . . . . .	93
4.7.3	HyViSI Well Depths . . . . .	97
<b>5</b>	<b>Silicon PIN Detectors in Astronomy</b>	<b>98</b>
5.1	Observations with the Kitt Peak 2.1m Telescope . . . . .	98
5.2	Data Reduction and Calibration . . . . .	100
5.2.1	Data Reduction Theory . . . . .	100
5.2.2	Reference Pixel Correction . . . . .	102
5.2.3	Dark Subtraction . . . . .	103
5.2.4	Slope Fitting . . . . .	103
5.2.5	Flat Fielding . . . . .	105
5.2.6	Combining Dithers . . . . .	106
5.2.7	Telescope Calibration with Multiple Windows . . . . .	106
5.2.8	Expected Point Spread Function . . . . .	108
5.3	Photometry . . . . .	112
5.3.1	Aperture Photometry . . . . .	113
5.3.2	Crowded Field Photometry . . . . .	116
5.3.3	High Speed Photometry with Guide Windows . . . . .	118
5.3.4	Variability Measurements of BE Lyn . . . . .	118
5.4	Astrometry . . . . .	122
5.4.1	Sources of Astrometric Error . . . . .	123
5.4.2	Astrometric Reduction . . . . .	124
5.4.3	Astrometric Results with H2RG-32-147 and H1RG-022 . . . . .	125
5.4.4	Astrometric Results with H4RG-10-007 . . . . .	126
5.5	Telescope Guiding in Guide Mode . . . . .	127
5.5.1	Purpose of Experiment . . . . .	127
5.5.2	Results without Guide Mode . . . . .	128
5.5.3	Results with Guide Mode . . . . .	129
5.5.4	Comparison between Exposures with and without Guide Mode . . . . .	130
5.5.5	Saturated Pixels . . . . .	133
5.5.6	Summary of Results . . . . .	133
5.5.7	Discussion . . . . .	134

5.6	Near Infrared Response . . . . .	135
<b>6</b>	<b>Pixel and Electronic Crosstalk</b>	<b>137</b>
6.1	Pixel Crosstalk . . . . .	137
6.1.1	Mechanisms of Pixel Crosstalk . . . . .	138
6.1.2	Measurement via Cosmic Rays . . . . .	140
6.1.3	Measurement via Fe <sup>55</sup> . . . . .	150
6.1.4	Measurement via Single Pixel Reset . . . . .	160
6.2	Electronic Crosstalk . . . . .	168
6.2.1	Column Bleeding . . . . .	168
6.2.2	Output Coupling . . . . .	171
<b>7</b>	<b>Persistence in HyViSI Detectors</b>	<b>174</b>
7.1	Trap Theory . . . . .	174
7.1.1	Hole Capture and Release from Shallow Traps . . . . .	176
7.1.2	Hole and Electron Capture from Deep Level Traps . . . . .	178
7.2	Latent Images and Persistence . . . . .	180
7.2.1	Persistent Charge Emission . . . . .	181
7.2.2	Dependence on Flux and Fluence . . . . .	186
7.2.3	Dependence on Detector Activity . . . . .	191
7.2.4	Dependence on Temperature . . . . .	192
7.2.5	Dependence on $V_{SUB}$ . . . . .	194
7.3	Semi-Permanent Offsets: Laser Burn-In . . . . .	198
7.4	Effect of Forward Biasing . . . . .	201
7.4.1	Theory of Bias-Direction Switch . . . . .	201
7.4.2	Forward Bias to Full Reverse Bias of $V_{SUB} = 15V$ . . . . .	202
7.4.3	Incrementing Reverse Bias with $\Delta V_{SUB} = 2V$ . . . . .	205
7.5	Model, Simulations, and Summary . . . . .	207
7.5.1	Phenomenological Description . . . . .	207
7.5.2	Persistence Simulations . . . . .	209
7.5.3	Summary . . . . .	214
7.6	Dealing with Persistence . . . . .	217
7.6.1	Persistence Reduction by Design . . . . .	217
7.6.2	Reduction After Design . . . . .	218
<b>A</b>	<b>Data Reduction</b>	<b>222</b>
A.1	IRAF Parameters . . . . .	222
<b>B</b>	<b>Signal to Noise Ratio</b>	<b>223</b>

<b>C Numerical Simulations</b>	<b>224</b>
C.1 PN Junctions . . . . .	224
C.2 Basic Semiconductor Physics . . . . .	224
C.3 Numerical Methods: Finite Volume Scheme . . . . .	225
C.4 Results for Abrupt PN Junction . . . . .	229
C.5 Cylindrically Symmetric Persistence Simulations . . . . .	233
<b>D Conversion Gain Reference</b>	<b>236</b>
<b>Bibliography</b>	<b>238</b>

# List of Tables

3.1	$C_{FAC}$ Values for Individual Detectors . . . . .	48
3.2	SIDECAR Conversion Gain Table . . . . .	55
3.3	SIDECAR Clocking Table for Averaging Multiple Channels . . . . .	56
3.4	SIDECAR Operating Parameters at Different Sampling Rates . . . . .	59
4.1	HyViSI Detectors Tested in the Laboratory . . . . .	64
4.2	Pixel Type Fractions for HyViSI Detectors Tested . . . . .	67
4.3	Fe <sup>55</sup> Lines from Radioactive Decay . . . . .	71
4.4	Conversion Gains, Nodal Capacitances, and Well Depth of HyViSI Devices . . . . .	73
4.5	HyViSI Well Depths . . . . .	97
5.1	Details for Observing Runs at Kitt Peak 2.1m Telescope . . . . .	98
5.2	Filter Characteristics . . . . .	99
5.3	Measured Magnitude for Landolt Standards . . . . .	114
5.4	Magnitude Transformation Equations for Landolt Standards . . . . .	115
5.5	Parameters from M13 Exposures . . . . .	116
5.6	Variability Parameters for the Delta Scuti Star BE Lyn . . . . .	119
5.7	Comparison of Astrometric Error with and without Guiding . . . . .	126
5.8	Comparison of Guide Mode vs. No Guiding . . . . .	133
6.1	Pixel Crosstalk Parameters for H2RG-001 . . . . .	155
7.1	Parameters for Core-Halo Simulation . . . . .	212

# List of Figures

1.1	Multi-Color Image of M13 Globular Cluster Taken with HyViSI H4RG-10-007 . . . . .	3
1.2	Simple Diagram of a $4 \times 4$ CCD . . . . .	4
1.3	Illustration of the Process of Clocking in a CCD . . . . .	7
1.4	Cartoon of CCD Destructive Readout . . . . .	8
1.5	Simplified Diagram of Passive and Active CMOS Pixel Architecture . . . . .	13
1.6	Simplified Diagram of CMOS Multiplexer and 3T Pixel . . . . .	15
1.7	Diagram of Per-Pixel Depleted and Fully Depleted Hybrid CMOS Arrays . . . . .	17
2.1	Diagram of PIN Diode . . . . .	25
2.2	Circuit Equivalent of a PIN Diode . . . . .	27
2.3	Resistivity of Silicon as a Function of Doping Density . . . . .	28
2.4	Image and Cross Section Diagram of HyViSI detector . . . . .	29
2.5	Diagram of PIN Diodes in a HyViSI Detector . . . . .	30
2.6	PIN Diode Quantities for Backside Voltage $V_{SUB} = 0 - 10V$ . . . . .	32
2.7	PIN Diode Quantities for Backside Voltage $V_{SUB} = 15 - 35V$ . . . . .	33
2.8	A Mock Schematic of the Full HyViSI Pixel . . . . .	34
2.9	PIN Diode as Capacitor During and After Reset . . . . .	35
2.10	HyViSI Pixel Circuit Equivalent . . . . .	37
2.11	Lateral Diffusion and Blooming in an Undepleted Detector . . . . .	39
3.1	Ramp Sequence Diagram and Clocking Patterns for HxRG Multiplexers . . . . .	41
3.2	Window Mode Diagram . . . . .	43
3.3	Signal of Science and Reference Pixels for H1RG-022 with no $C_{FAC}$ . . . . .	45
3.4	Difference of Science and Reference Pixels for H1RG-022 . . . . .	46
3.5	Slope Error with $C_{FAC}$ . . . . .	47
3.6	Difference of Science and Reference Pixels for H1RG-022 after Applying $C_{FAC}$ . . . . .	48
3.7	SIDECAR ASIC Block Diagram and Photograph . . . . .	50
3.8	SIDECAR ASIC Development Kit in RIT Laboratory . . . . .	51
3.9	SIDECAR Amplification Stage . . . . .	52

3.10	SIDECAR Noise Images: Reset Schemes . . . . .	53
3.11	SIDECAR Conversion Gain . . . . .	54
3.12	Multiple Channels Averaged in SIDECAR . . . . .	57
3.13	Read Noise of H1RG-022 with Multiple Channels Averaged . . . . .	58
3.14	SIDECAR Images and Histograms with Non-ideal Operating Parameters . . . . .	61
4.1	Dewar Used at Rochester Imaging Detector Laboratory . . . . .	63
4.2	Flat Field Image Showing Open Pixels . . . . .	67
4.3	Diagram of Unit Cell, Bus Lines, and Output of H2RG . . . . .	69
4.4	Electronic Gain for H1RG-022 . . . . .	70
4.5	Fe55 Histogram for H2RG-001 . . . . .	72
4.6	Temperature Dependence of Conversion Gain with Constant $V_{BIASGATE}$ . . . . .	74
4.7	Simplified Diagram of Noise Associated with Resetting Pixels . . . . .	75
4.8	Up the Ramp Exposure Diagram with Fowler Sampling . . . . .	80
4.9	CDS Read Noise Map for H2RG-001 at 100 K . . . . .	81
4.10	Temperature Dependence of CDS Read Noise for H2RG-001 . . . . .	82
4.11	Read Noise vs. Fowler Pair and Temperature Dependence for H2RG-001 . . . . .	83
4.12	Dark Current Histogram for H1RG-022 . . . . .	85
4.13	Dark Current vs. Temperature for HyViSI Detectors . . . . .	86
4.14	Pixel Ramp Showing Reset Anomaly in H1RG-022 . . . . .	88
4.15	Reset Anomaly at Different Reset Voltages . . . . .	89
4.16	Detective Quantum Efficiency of H4RG-10-007 . . . . .	91
4.17	Fringing in Monochromatic Flat Field near $1 \mu\text{m}$ . . . . .	91
4.18	Photon Transfer Curves for H2RG-32-147 with Output Source Follower Enabled . . . . .	93
4.19	Linearity of H2RG-32-147 and H2RG-001 as a Function of Electrons Integrated on Nodal Capacitance. . . . .	96
5.1	Photograph of RIDL Dewar Mounted to Kitt Peak 2.1m Telescope . . . . .	99
5.2	Drift of Telescope from Sidereal Tracking Rate . . . . .	108
5.3	Expected Ellipticity and FWHM in Guiding and Unguided Operation . . . . .	111
5.4	Magnitude Plot for Landolt Photometric Standards . . . . .	115
5.5	M13 Color Magnitude Diagram in $g$ and $i$ . . . . .	117
5.6	M13 Color Magnitude Diagram in $g$ and $y$ . . . . .	117
5.7	Magnitude vs. Time for BE Lyn and Reference Star GSC 03425-00544 . . . . .	120
5.8	Magnitude vs. Time for BE Lyn after Normalization by Reference Star and Filtering . . . . .	121
5.9	Astrometric Error vs. Exposure Time for H2RG-32-147 Observations of Open Cluster NGC 956 . . . . .	125
5.10	Long Time Exposure Taken with H1RG-022 with No Guiding . . . . .	129

5.11	Long Time Exposure Taken with H2RG-32-147 in Guide Mode . . . . .	130
5.12	Comparison of Long Time Exposures With and Without Telescope Guiding . . . . .	131
5.13	Exposure Time Required to Reach Limiting Magnitude . . . . .	132
5.14	Interpixel Capacitance of Guide Window with Surrounding Pixels . . . . .	134
5.15	Tri-color Image of Orion Nebula Showing Near IR Response . . . . .	136
6.1	Cosmic Ray Ramps and Decay of Signal After Incidence . . . . .	141
6.2	Charge Lost by Pixel in 800 Seconds as a Function of Charge Deposited by Cosmic Ray . . . . .	144
6.3	Histograms of Time Constant $c_n$ in Cosmic Ray Decays for Different Temperatures . . . . .	145
6.4	Muon Track Showing Different Charge Loss at Opposing Ends . . . . .	146
6.5	Dependence of Charge Loss on Depth of Interaction for Extended Muon Tracks . . . . .	147
6.6	Cosmic Ray Pixels Sharing Charge . . . . .	148
6.7	No Coupling of Reference Pixels to Science Pixels During Cosmic Ray Event . . . . .	149
6.8	Examples of Single and Multiple Pixel Events from Fe <sup>55</sup> Exposure . . . . .	151
6.9	Examples of Fe <sup>55</sup> Distributions from Guess and Check Iteration Process . . . . .	153
6.10	Pixel Crosstalk vs. Temperature for H2RG-001 . . . . .	155
6.11	Fe <sup>55</sup> Ramps Showing Charge Loss . . . . .	156
6.12	Pictorial Plot Showing Loss of Charge After Fe <sup>55</sup> Hit . . . . .	157
6.13	Shift and FWHM of Fe <sup>55</sup> Peak in temperature range 140-170 Kelvin . . . . .	159
6.14	The Effect of Charge Loss on Fe <sup>55</sup> Spectrum at 170 K . . . . .	159
6.15	Pixel Crosstalk with Single Pixel Reset . . . . .	162
6.16	The Effect of Single Pixel Reset on Column Voltage . . . . .	163
6.17	Charge Diffusion and Persistence in Single Pixel Reset Experiments at Temperatures from 100-180 K . . . . .	164
6.18	Signal Measured for Pixel Subject to Single Pixel Reset as a Function of V <sub>RESET</sub> . . . . .	166
6.19	Zoom-in of Signal Measured for Pixel Subject to Single Pixel Reset as a Function of V <sub>RESET</sub> . . . . .	167
6.20	Column Bleeding in Horsehead Nebula Mosaic Taken with H2RG-32-147 . . . . .	168
6.21	Star Showing Column Bleeding and Threshold . . . . .	169
6.22	Output Coupling in Mosaic of SAO 117637 Taken with H2RG-32-147 . . . . .	171
6.23	Output Coupling Circuit Diagram . . . . .	172
6.24	Output Coupling with No Source Follower . . . . .	173
7.1	Saturn: Saturated and Persistent Images . . . . .	180
7.2	Temporal and Spatial Evolution of Persistence Structure . . . . .	183
7.3	Diagram of Core-Halo Persistence Structure . . . . .	184
7.4	Ramps for Pixels in Region Surrounding Persistence Center . . . . .	185

7.5	Maximum Persistence Signal in 14 Second Exposure . . . . .	187
7.6	Minimum Persistence Signal in 14 Second Exposure . . . . .	188
7.7	Decay of Dark Current in Core-Halo Persistence . . . . .	190
7.8	Histograms of Time Constants for Latent Image Decays . . . . .	190
7.9	Latent Image Lasting More than One Hour . . . . .	191
7.10	Pixel Ramp Showing Reset Anomaly in H1RG-022 . . . . .	193
7.11	Latent Images at Different Values of $V_{SUB}$ . . . . .	195
7.12	Stored and Excess Hole Populations Under Saturation in Undepleted Detector . . . . .	197
7.13	Semi-Permanent Offset in H2RG-32-147 Burned in by Mars . . . . .	198
7.14	6 Month Decay of Laser Burn-In on H2RG-32-029 . . . . .	200
7.15	Dark Current after Forward Bias and Return to Reverse Bias in H1RG-022 . . . . .	204
7.16	Dark Current after Increasing $V_{SUB}$ in H1RG-018 . . . . .	205
7.17	Toy Model of Charge Density, Electric Field, and Electric Potential in PIN Diode . . . . .	208
7.18	Drift and Diffusion Currents Responsible for Negative Persistence . . . . .	210
7.19	Comparison of Ramps and Radial Profiles for Simulated Persistence and Real Data . . . . .	212
7.20	Comparison of Simulated Hole and Electron Distributions with and without Drift . . . . .	214
7.21	Dither Sequence Showing Persistence in all Dither Locations . . . . .	219
C.1	PN Junction Diagram . . . . .	226
C.2	Results for PN Junction with No Applied Bias . . . . .	231
C.3	Results for PN Junction Under Reverse Bias . . . . .	232